

# **IDRONATURAL**

di Casella Maurizio – tel. 338/44.63.654



UNDERSLINK SYSTEM WATER TREATMENT

## **MODEL IDROSTAL**

Steel powder coated chassis. LCD display with adjustable horizontally or vertically which allow the control and regulation of the functional phases in the machinery. Easy opening for maintenance (single crew). The smaller on the market today. Beautiful elegant without external screws (fastening with internal captive screws).

N° 1 sedimenti filter.

N° 1 carbon block filter.

Membrane: N° 2 -150 GPD

Exclusive water cooled engine – power 180 W (does not heat, can be used continuously also in closed places without air recirculation),

Pump fluid-o-tech 300 lt/h

Electronic control unit: filters, conductivity, anti-flooding sensor, engine, delay, ignition, shut-down. recirculation system. Automatic flushing.

### TECHNICAL CHARACTERISTICS

Nominal production : 90-110 lt/h (production varies with salinity, net pressure, and water temperature).

Working pressure 9-10 bar.

Power supply 230 V – 50 Hz.

Dimensioni: L/P/H 105 X 385 X 385 mm

**IDRONATURAL** 

[www.idronatural.com](http://www.idronatural.com) – e-mail: [idronatural@gmail.com](mailto:idronatural@gmail.com) – P.IVA: 01479700054